



by Honeywell

Technical Specifications

Miller H-Design 2pts Harness w/Auto. b. & 2 D rings

Description:

Miller H-Design 2 points harness with 2 D rings at the sternal point + the back side and automatic buckles on chest and legs straps.

The Miller H-Design harnesses are the new generation of harnesses dedicated to construction and general industry sectors providing more comfort, freedom of movements and safety to workers.

Fall indicator on the Front side



References:

1032850	H-Design 2pts w/auto. buckles 2 D size 0
1032851	H-Design 2pts w/ auto. buckles 2 D size 1
1032852	H-Design 2pts w/ auto. buckles 2 D size 2
1032853	H-Design 2pts w/ auto. buckles 2 D size 3

SIZE SELECTION GUIDE



Images are for guidance only.

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com

Benefits:

COMFORT AND FREEDOM OF MOVEMENTS

- Exclusive H architecture of the harness, thanks to its ergonomically placed webbing, providing a total freedom of movements for the arms.
- Horizontal leg straps preventing uncomfortable friction on the legs and on the groin (vs traditional leg straps) increasing comfort for the user during work.

EASY AND QUICK ADJUSTABILITY & CONNECTION

- Easy to access and adjust buckles: intuitive movement up to down.
- Very accessible anchor points: bended position back D-ring
- Adjustable chest strap for a perfect fit in height and width.
- Adjustable leg straps.
- Easy Front strap clip.
- Sternal point with D ring.

GREATER SAFETY AND EASIER TRACEABILITY:

- Fluo green textile, high visible stitching, front and back fall indicators to facilitate visual inspection before working.



**Fall indicators
on the back plate
for easy inspection**

- Labels improving yearly checking follow-up for a better traceability
- Water-repellent and stain free webbing for greater product durability.
- Hi-visibility vest (option) to see workers even in dark environments (EN ISO 20471)



by Honeywell

Features :

Shoulder Straps :

Standard green 44 mm webbing.
PES with PTFE treatment (water repellent / anti stain)
Breaking strength : > 2700 daN

Other Straps :

Standard black webbing 44 mm
PES with PTFE treatment (water repellent / anti stain)
Breaking strength : > 2700 daN

Back Anchorage D-ring :

Material : steel
Finish : Zinc plated Silver
Breaking strength : > 2300 daN

Sternal point : D ring.

Material : steel
Finish : Zinc plated
Breaking strength : > 2 800

Aluminium automatic buckles :

Breaking strength : > 900 daN

Steel mating buckles :

Finish : Zinc plated Silver
Breaking strength : > 900 daN

Weights

Ref	Designation	Weight (kg)
1032850	H-Design 2pts w/ auto. buckles 2 D size 0	1,13
1032851	H-Design 2pts w/ auto. buckles 2 D size 1	1,15
1032852	H-Design 2pts w/ auto. buckles 2 D size 2	1,17
1032853	H-Design 2pts w/ auto. buckles 2 D size 3	1,19

Breaking strength: > 15 KN
Temperature: -30°C to +50°C

EN 361 Full Body Harnesses

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com