



PRODUCT NUMBER: 1032856
Miller H-Design® Duraflex™ 1
pt harness Mating - size 2

Miller H-Design® Duraflex™ 1 point harness with Stretched shoulder straps and mating buckles -Size 2.



Overview

Reference Number

1032856

Product Type

Fall Protection

Range

Harness

Brand

Miller by Honeywell

Industry

- Building and Construction
- General Industry
- Telecoms
- Utilities

Product Use

The Miller H-Design® harnesses are the new generation of harnesses dedicated to construction and general industry sectors providing more comfort, freedom of movements and safety to workers.

Features & Benefits

Feature

Shoulder Straps : Duraflex Stretch 44,5 mm webbing PES with PTFE treatment (water repellent / anti stain) Colour : green with a black drawing Breaking strength :-> 2200 daN

Feature

Other Straps : Standard black webbing 44 mm PES with PTFE treatment (water repellent / anti stain) Breaking strength :-> 2700 daN

Feature

Back Anchorage D-ring : Material : steel Finish : Zinc plated Silver Breaking strength :-> 2300 daN

Feature

Mating buckles : Material : steel Finish : Zinc plated Silver Breaking strength :-> 900 daN

Feature

Weights : 1 Kg Breaking strength: > 15 KN Temperature: -30°C to +50°C EN 361 Full Body Harness

Feature

Certified for maximum load of 140 Kgs.

Certifications

 E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Attestation

 EC Type examination certificate 1032854 - 1032855 - 1032856 - 1032857

EC Attestation Number

0082/490/160/05/14/0141

Certifications

- EN 361

Literature & Documents

1032854-1032855-1032856-1032857 Data Sheet EN

http://www.honeywellsafety.com/supplementary/documents_and_downloads/fall_protection/full_body_harness/4294983954/1033.aspx

Additional Information

User Manual

NT90023600 IND B

Maintenance

Life Cycle

Life expectancy of our harnesses is 10 years from the date of manufacture.

Storage Information

Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Care Instructions

Please remember that:

- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.

Packaging

EAN Code

63079098

Country of Origin

France



Centre d'Essais de Fontaine
17, Boulevard Paul Langevin
38600 FONTAINE - France
Tél. +33.(0)4.76.53.52.22
Fax +33.(0)4.76.53.32.40

En exécution de la directive 89/686/CEE du 21 décembre 1989 modifiée concernant le rapprochement des législations des états membres relatives aux équipements de protection individuelle et des dispositions pertinentes du code du travail, portant transposition de cette directive en droit français,
In enforcement of amended directive 89/686/EEC of 21st of December 1989 on the approximation of the laws of the Members States relating to personal protective equipment and in enforcement of relevant requirements of the French labour code, providing for the transcription of this directive into French regulations,

APAVE SUDEUROPE SAS, organisme notifié identifié sous le numéro 0082, attribue l'
APAVE SUDEUROPE SAS, notified body, identified under number 0082, awards the

ATTESTATION D'EXAMEN (CE) DE TYPE
(CE Type examination certificate)
N° 0082/490/160/05/14/0141

A l'équipement suivant :
To the following equipment

➤ Type d'équipement : **EPI de catégorie III – Harnais antichute**
Category of equipment PPE category III – Full body harness

➤ Marque commerciale : **MILLER®**
Trademark

Modèle : **H-DESIGN DURAFLEX 1PT RAPCO**
Model

➤ Equivalences : la présente attestation est attribuée aux 5 tailles suivantes :
Equivalences: this certificate is awarded to the following 5 sizes

- **Taille 0** – Très petite taille
Size 0 - Extra small size
- **Taille 1** – Petite taille
Size 1 - Small size
- **Taille 2** – Taille moyenne
Size 2 - Medium size
- **Taille 3** – Grande taille
Size 3 - Large size
- **Taille 4** – Très grande taille
Size 4 - Extra large size

➤ Fabricant : **HONEYWELL FALL PROTECTION France SAS – 35-37 rue de la Bidauderie – 18100 VIERZON – France**
Manufacturer

➤ Description : Harnais d'antichute à un point d'accrochage antichute dorsal par dé métallique référence 90023604. Fermeture de la bavaroise et des tours de cuisses par boucles métalliques mâle/femelle référence 90023603 et 90023602. Réglage des bretelles par boucles métalliques mâle/femelle référence 90023603 et 90023602. Ce harnais antichute à également été testé à 140kg (description détaillée dans le rapport d'examen CE de type 14.6.0252).

Description Full body harness including one back fall arrest attachment point by metallic D-ring reference 90023604. Front webbing and leg loops attachment by metallic male/female buckles reference 90023603 and 90023602. Shoulder strap front adjustment by metallic male/female buckles reference 90023603 and 90023602. This full body harness was also tested for 140kg (detailed description in EC type examination report 14.6.0252).

➤ Référentiel technique utilisé : **EN 361:2002**
Technical referential in use

Date : le 19 mai 2014
Date the 19th May 2014

Document authentifié par tampon sec
Document certified by dry stamp

Le Responsable du Centre d'Essais de Fontaine – Certification EPI
Head of Fontaine Testing Center – PPE Certification


Vincent MAILLOCHEAU

NOTA : Toute modification apportée au matériel neuf objet de la présente attestation d'examen CE de type doit être portée à la connaissance de l'organisme habilité en application de l'article R4313-38 du code du travail.
Any modification brought about a new equipment covered by this CE type examination certificate must be notified to the body in enforcement of article R4313-38 of French labour code.

Cette attestation comporte une page. Elle est établie en deux exemplaires originaux transmis au demandeur. Aucun duplicata ne sera délivré.
This certificate includes one page. This certificate is edited in two original copies. No duplicate will be issued.



E.C. Declaration of Conformity

The manufacturer or its legal representative supplier in the European Community:

Honeywell Safety Products Europe

Declares that the Personal Protective Equipment described here after conforms to the provisions of the European Council Directive 89/686/CEE:

Designation: Miller H-Design® Duraflex™ 1 pt harness Mating - size 2

Reference: 1032856

Standard(s): EN361

This PPE is the object of the below EC examination certificate n°:

And is subject to the procedure set out in Article 11 point B of Directive 89/686/EEC under the supervision of the below notified body.

Delivered by:

APAVE SUDEUROPE SAS

BP 3

33370

ARTIGUES près BORDEAUX

France

Drawn up in , on the 26/02/2017

By: Frederic Wagner

Division: Fall Protection

ZI Paris Nord II 33, rue des Vanesses BP 50288 95958 Roissy CDG France

Tel: +33 (0) 49 90 79 79 Fax: +33 (0)1 49 90 79 80

www.honeywellsafety.com



by Honeywell

Technical Specifications

Miller H-Design Duraflex™ 1pts Harness

Description:

Miller H-Design 1 point harness with Stretched shoulder straps and mating buckles.

The Miller H-Design harnesses are the new generation of harnesses dedicated to construction and general industry sectors providing more comfort, freedom of movements and safety to workers.



References:

1032854	H-Design Duraflex 1pt mating buckle size 0
1032855	H-Design Duraflex 1pt mating buckle size 1
1032856	H-Design Duraflex 1pt mating buckle size 2
1032857	H-Design Duraflex 1pt mating buckle size 3

SIZE SELECTION GUIDE



HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com

Benefits:

COMFORT AND FREEDOM OF MOVEMENTS

- Exclusive H architecture of the harness, thanks to its ergonomically placed webbing, providing a total freedom of movements for the arms.
- Horizontal leg straps preventing uncomfortable friction on the legs and on the groin (vs traditional leg straps) increasing comfort for the user during work.
- Stretch webbing on the shoulders to provide even more comfort.

EASY AND QUICK ADJUSTABILITY & CONNECTION

- Easy to access and adjust buckles: intuitive movement up to down.
- Very accessible anchor points: bended position back D-ring
- Adjustable chest strap for a perfect fit in height and width.
- Adjustable leg straps.
- Easy Front strap clip.



GREATER SAFETY AND EASIER TRACEABILITY:

- Fluo green textile, high visible stitching, back fall indicators to facilitate visual inspection before working .



**Fall indicators
on the back plate
for easy inspection**

- Labels improving yearly checking follow-up for a better traceability
- Water-repellent and stain free webbing for greater product durability.
- Hi-visibility vest (option) to see workers even in dark environments (EN ISO 20471)



by Honeywell

Features :

Shoulder Straps :

Duraflex Stretch 44,5 mm webbing
PES with PTFE treatment (water repellent / anti stain)
Colour : green with a black drawing
Breaking strength : > 2200 daN

Other Straps :

Standard black webbing 44 mm
PES with PTFE treatment (water repellent / anti stain)
Breaking strength : > 2700 daN

Back Anchorage D-ring :

Material : steel
Finish : Zinc plated Silver
Breaking strength : > 2300 daN

Mating buckles :

Material : steel
Finish : Zinc plated Silver
Breaking strength : > 900 daN

Weights :

Ref	Designation	Weight (kg)
1032854	H-Design Duraflex 1pt mating size 0	0,96
1032855	H-Design Duraflex 1pt mating size 1	0,98
1032856	H-Design Duraflex 1pt mating size 2	1,00
1032857	H-Design Duraflex 1pt mating size 3	1,02

Breaking strength: > 15 KN
Temperature: -30°C to +50°C
EN 361 Full Body Harnesses

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com