



by Honeywell

Technical specifications

Miller DuraSeal™ Self Retracting Lifeline

Description

The patent-pending Miller DuraSeal™ Self-Retracting Lifeline (SRL) is designed to perform in the harshest environments including onshore and offshore oil and gas, mining and petrochemical applications. The DuraSeal's sealed technology, reusable brake system, field replaceable lifeline and corrosion resistant materials keep the product in the field to lower cost of ownership.

Key Competitive Advantages:

- Prevents contaminants from entering the unit with highest industry rated sealed technology IP69K
- Built to last reusable brake design withstands multiple falls
- Quick, low cost repair with field replaceable lifeline
- Reduces fatigue and increases productivity with units up to 30% lighter than competitive sealed units
- Enables, quicker easier installation and provides protection from rain

Product service life is extended in the harshest environments with corrosion resistant components

REFERENCES :

Ref 1034130-E : DuraSeal™ 15 M Galva

Ref 1034131-E : DuraSeal™ 15 M Stainless Steel



HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com



by Honeywell

Features

Housing: Cast Aluminum

Cable: Stainless Steel or Galvanized Steel 5mm

Technical

Max. Capacity: 140 kg

Max. Working Length: 15 m

Max. Total Arrest Distance: 1.1 m

Certification :

EN 360

IEC 60529: International Protection Rating/Ingress

Protection Ratings - IP68, Protected from total ingress. Dust tight and protected against 1m immersion in water.

ISO 20653: Road vehicles - Degrees of protection (IP code) - IP69K, Protected from total ingress. Dust tight and protected against high pressure, steam-jet cleaning.

Weight : 12 kgs

Temperature : -30°C to +50°C

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com