



PRODUCT NUMBER: 23-0913B
Honeywell CoreShield™
Gloves - 23-0913B

CoreShield, 13 gauge nylon black liner, nitrile black thin coating, A3/C



Overview

Reference Number

23-0913B

Product Type

Gloves

Line

Cut resistant

Brand

Honeywell

Industry

- Automotive and Part Manufacturer
- Building and Construction
- Glass Industries
- Logistics
- Metal steel

Features & Benefits

Feature

CoreShield™ Engineered Yarn

Benefit

One of the lightest cut-protective gloves in the market, help to prevent hand fatigue for workers who need to wear them all day long. Skin-friendly yarns that reduce allergy and provide excellent dexterity

Feature

CoreShield™ High Performance Nitrile coating

Benefit

Reduced hand fatigue and excellent dexterity.

Feature

Color-coded marking system

Benefit

For easy gloves selection you need for your application

Feature

Thumb reinforcement

Benefit

For greater wear resistance and extended product life

Feature

Washable

Benefit

Reduced cost of ownership

Feature

Hand and wrist protection

Benefit

A longer cuff ensures wrist protection

Feature

Touchscreen resistive and capacitive

Benefit

To operate touch panels of industrial machines and smartphone touchscreens without taking their gloves off

Feature

Gauge 13

Benefit

For a great fit/dexterity

Technical Description

Description

CoreShield, 13 gauge nylon black liner, nitrile thin black

Product Technology

Correshield Engineered yarn and high performance thin Nitrile coating

Fiber

Basalt, Nylon

Gauge

13

Glove/liner color

Black

Coating Type

Nitrile thin

Coating Color

Black

Length

255mm size 9

Sizes

6XS - 11XXL

EN 407 - Heat and/or Fire

| | |
|-------------------------------------|---|
| Behaviour and/or fire | X |
| Resistance to contact heat | 1 |
| Resistance to convective heat | X |
| Resistance to radiant heat | X |
| Resistance to small metal splashes | X |
| Resistance to molten metal splashes | X |

EN 388 - Mechanical Hazards Abrasion Resistance

| | |
|---------------------------------|---|
| Abrasion resistance | 4 |
| Cutting resistance (Coupe test) | X |

| | |
|-------------------------------|---|
| Tear resistance | 4 |
| Puncture resistance | 3 |
| Cutting resistance (TDM test) | C |

ASTM D3389-05

| | |
|--------------------------------|---|
| ANSI Level Abrasion Resistance | 6 |
|--------------------------------|---|

ASTM F1790-97

| | |
|---------------------------|----|
| ANSI Level Cut Resistance | A3 |
|---------------------------|----|

Packaging Label

UOM
Pairs

Literature & Documents

CoreShield Smooth Nitrile Data Sheet UK
http://www.honeywellsafety.com/supplementary/documents_and_downloads/secured/gloves/4295003655/1033.aspx

Packaging

Unit of Measure
PAA

Quantity per Box/Pack/Case
10

Quantity per Carton
100

Quantity for Minimum Order
100

Country of Origin
China